

## SPECIFICATIONS KYUSHU ZWARTHOUT I SHOU SUGI BAN JANUARY 2022

### 45.31.10-A CARPENTRY, FRAMEWORK, SAWN WOOD

#### 0. CARPENTRY FRAMEWORK

Framework: preserved,  
Vertical or horizontal, bevelled  
painted black for open wall cladding  
Frame distance (c.t.c.) (m): max. 0.6  
Joints: mechanical fastening with screws

#### 1. SAWN CONIFEROUS WOOD (NEN 5466+a03)

Zwarthout I Shou Sugi Ban

Supplier: Zwarthout I Shou Sugi Ban

[www.zwarthout.com](http://www.zwarthout.com)

[contact@zwarthout.com](mailto:contact@zwarthout.com)

Middelweg 85

3956TL Leersum, the Netherlands

+31 343 76 89 59

Wood product Pinus Radiata, thermally modified or acetylated dosage, burned, brushed, stained

Certification FSC

Quality grade: A2

Surface treatment: Zwarthout I Shou Sugi Ban, Kyushu, Pinus Radiata, thermally modified or acetylated dosage, burned, brushed, stained

Profile: as approved sample

Thickness (mm): 16-22 mm nominal

Width (mm): 50-200 mm

Moisture content (%): 5-15

Coating: Bitu Black matt

Fastening materials:

- 410 stainless steel screws 4x50 black head (length 2.5 x plank thickness)
- black-headed nails