

SPECIFICATIONS NAKATADO ZWARTHOUT I SHOU SUGI BAN JANUARY 2022

45.31.10-A CARPENTRY, FRAMEWORK, SAWN WOOD

0. CARPENTRY FRAMEWORK

Framework: preserved,
Vertical or horizontal, bevelled
painted black for open wall cladding
Frame distance (c.t.c.) (m): max. 0.6
Joints: mechanical fastening with screws

1. SAWN CONIFEROUS WOOD (NEN 5466+a03)

Zwarthout I Shou Sugi Ban

Supplier:	Zwarthout I Shou Sugi Ban www.zwarthout.com contact@zwarthout.com Middelweg 85 3956TL Leersum, the Netherlands +31 343 76 89 59
Wood product	Pinus Radiata, thermally modified or acetylated dosage, burned, brushed, stained
Certification	FSC
Quality grade:	A2
Surface treatment: type	Zwarthout I Shou Sugi Ban, Nakatado, Pinus Radiata, thermally modified or acetylated dosage, burned, brushed, stained
Profile:	as approved sample
Thickness (mm):	16-22 mm nominal
Width (mm):	50-200 mm
Moisture content (%):	5-15
Coating:	Bito Black matt

Fastening materials:

- 410 stainless steel screws 4x50 black head (length 2.5 x plank thickness)
- black-headed nails